Coast Guard, DHS § 160.077–6

(2) Each Type V commercial hybrid

[CGD 78-174, 50 FR 33928, Aug. 22, 1985. Redesignated and amended by CGD 78-174, 60 FR 2486, Jan. 9, 1995]

§160.077-4 Type.

- (a) A hybrid PFD that successfully passes all applicable tests may be approved as a Type I, II, III, or V for various size ranges of persons weighing over 23 kg (50 lb), as Type I or II for persons weighing 14–23 kg (30–50 lb) or as Type I or II for other sizes. A Type V PFD has limitations on its approval.
- (b) The approval tests in this subpart require each Type V hybrid PFD to have at least the same performance as a Type I, II, or III PFD for adult and youth sizes or Type I or II PFD for child sizes.
- (c) A hybrid PFD may be approved for use on recreational boats, commercial vessels or both if the applicable requirements are met.

[CGD 78-174, 60 FR 2486, Jan. 9, 1995]

§ 160.077-5 Incorporation by reference.

- (a) Certain materials are incorporated by reference into this subpart with the approval of the Director of the Federal Register. The Office of the Federal Register publishes a table, "Material Approved for Incorporation by Reference," which appears in the Finding Aids section of this volume. In that table is found the date of the edition approved citations to the particular sections of this part where the material is incorporated, addresses where the material is available, and the date of approval by the Director of the Federal Register. To enforce any edition other than the one listed in the table, notice of the change must be published in the FEDERAL REGISTER and the material made available to the public. All approved material is on file at the Office of the Federal Register, Washington, DC 20408, and at the U.S. Coast Guard, Lifesaving and Fire Safety Division (CG-ENG-4).. 2100 2nd St., SW., Stop 7126, Washington, DC 20593-7126.
- (b) The materials approved for incorporation by reference in this subpart are:

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

- 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.
 - ASTM B 117-97, Standard Practice for Operating Salt Spray (Fog) Apparatus— 160.077-11
- ASTM D 751-95, Standard Test Methods for Coated Fabrics—160.077-19
- ASTM D 1434-82 (1988), Standard Test Method for Determining Gas Permeability Characteristics of Plastic Film and Sheeting—160.077-19

FEDERAL STANDARDS

- In Federal Test Method Standard No. 191 the following test methods:
 - (1) Method 5100, Strength and Elongation, Breaking of Woven Cloth; Grab Method.
 - (2) Method 5132, Strength of Cloth, Tearing; Falling-Pendulum Method.
 - (3) Method 5134, Strength of Cloth, Tearing; Tongue Method.
 - (4) Method 5804.1, Weathering Resistance of Cloth; Accelerated Weathering Method.
- (5) Method 5762, Mildew Resistance of Textile Materials; Soil Burial Method.
- Federal Standard No. 751, Stitches, Seams, and Stitching.

MILITARY SPECIFICATIONS

MIL-L-24611(SH)—Life Preserver Support Package For Life Preserver, MK 4. NATIONAL BUREAU OF STANDARDS (NBS)

"The Universal Color Language" and "The Color Names Dictionary" in Color: Universal Language and Dictionary of Names, National Bureau of Standards Special Publication 440.

UNDERWRITERS LABORATORIES (UL.)

- UL 1191, "Components for Personal Flotation Devices."
- UL 1517, "Hybrid Personal Flotation Devices."

[CGD 78-174, 50 FR 33928, Aug. 22, 1985. Redesignated by CGD 78-174, 60 FR 2486, Jan. 9, 1995; CGD 95-072, 60 FR 50467, Sept. 29, 1995; CGD 96-041, 61 FR 50733, Sept. 27, 1996; USCG-1999-5151, 64 FR 67184, Dec. 1, 1999; USCG-2009-0702, 74 FR 49237, Sept. 25, 2009]

§ 160.077-6 Approval procedures.

- (a) General. Subpart 159.005 of this chapter contains the approval procedures. Those procedures must be followed, excepted as modified in this paragraph.
- (1) Preapproval review under §§ 159.005–5 and 159.005–7 may be omitted if a similar design has already been approved.
- (2) The information required in all three subparagraphs of §159.005–5(a)(2) must be included in the application.
- (3) The application must also include the following: